



Email: sales@endeavourmarine.com.au

Websites://www.endeavourmarine.com.au/

1 Nanda St Marmong Point NSW 2284



250 HP Sea Pro

POA

Specifications

Boat Details

Price POA Boat Brand Mercury
Model 250 HP Length 0.00

Year 2020 Category Boat Engines and Outboards

Hull Style Hull Type
Power Type Stock Number

Condition New State New South Wales

Suburb MARMONG POINT Engine Make Mercury

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.

Email: sales@endeavourmarine.com.au

Websites://www.endeavourmarine.com.au/

1 Nanda St Marmong Point NSW 2284

Description

The new Mercury V-8 SeaPro outboard models bring more of everything to the job—more displacement, more power, more efficiency and more durability. The impressive muscle of our new V-8 4.6-litre powerhead is specifically designed for commercial duty and delivers our best-ever fuel economy and FourStroke performance. The combination of ample torque and low weight makes these engines ideal for heavily-loaded boats. Guaranteed to do its job, so you can do yours. Mercury SeaPro FourStroke models come with a 2+1=3 year commercial factory warranty.ENGINE DETAILS

Offers simple, seamless repower rigging. Engineered for commercial fishing vessels, commercial workboats and law-enforcement boats.SPECIFICATIONS - 250

HP / kW

• 250/186

Engine type

• V-8

MidSection

Conventional MidSection

Displacement (CID/CC)

• 279 CID

Displacement (L)

• 4.6L

Cylinder Configuration

• V-8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves

Full throttle RPM

• 4800-5600

Air induction

• Performance-Tuned Long-Runner Intake Manifold

Fuel induction system

• Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization

Alternator amp / Watt

• 85-amp (1071 Watt) with Idle Charge

Recommended fuel


Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum

Recommended oil

• NMMA Certified FCW SAE 25W-40 (Optional 10W-30 for Cold Conditions)

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.





Email: sales@endeavourmarine.com.au

Websites://www.endeavourmarine.com.au/

1 Nanda St Marmong Point NSW 2284

Engine protection operator warning system

• SmartCraft Engine Guardian

Compatible with SmartCraft digital technology

Yes

Starting

• Electric Start with SmartStart Protection

Controls

Remote Mechanical or Digital Throttle & Shift (DTS)

Steering

- Big Tiller (optional)
- Hydraulic (standard)
- Power (optional)

Shaft length

- 20" / 508 mm
- 25" / 635 mm
- 30" / 762 mm

Gearcase ratio

• 1.75:1

Dry weight *Lightest model available

• 527 lbs / 239 kgs

CARB star rating

• 3

Bore and stroke

• 3.6 in x 3.4 in / 92 mm x 86 mm

Ignition

• SmartCraft PCM 112 Digital Inductive

Cooling system

• Water-cooled with thermostat

Gear shift

• F-N-R

Gearcase options


• 5.44"

Trim system

• Power trim and tilt

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.





Email: sales@endeavourmarine.com.au Websites://www.endeavourmarine.com.au/

1 Nanda St Marmong Point NSW 2284

Exhaust system

Through prop

Counter Rotation

Available

Color

• Phantom Black

Lubrication system

• Integrated wet sump

Oil Capacity

• 7.0 Quarts / 6.6 Liters

Maximum Trim Range

• 20° (-6° to 14°)

Maximum Tilt Range

• 73° (-6° to 67°)

Engine Details

Engine Make Mercury
Displacement 4.6
Horse Power 250

Disclaimer